

A highly modern machine outfit and the peripheral facilities and equipment assure the quality of demanding machined parts



Spritzgussautomaten

Typ	Amount	Clamping force (kN)	Tie bar distance (mm)	Part weight (g PS)	Special features
ARBURG					
270 S 250-60	1	250	270x270	33	Swivelling clamp 1 core puller, several movements possible at the same time
270 M 350-90	1	350	270x270	59	-
320 S 350-150	1	350	320x320	65	1 core puller, several movements possible at the same time
320 D 500-210	1	500	320x320	117	1 core puller
420 S 600-350	2	600	420x420	153	1 core puller each with several movements possible with integrated slug discharge
230 D 750-210	9	750	320x320	117	Partly 1 core puller
420 S 800-350	3	800	420x420	153	1 core puller each with several movements possible with integrated slug discharge
420 M 1000-350	2	1000	420x420	je 194	1 core puller each, several movements possible at the same time
420 C 1000-350	2	1000	420x420	je 153	1 core puller each, equipped with Geiger discharge handling XYZ
420 S 1000-350	1	1000	420x420	153	2 core pullers, integrated hot runner control loops, several movements possible at the same time
520 C 1300-675	1	1300	520x520	297	2 core pullers, several movements possible at the same time
520 M 1600-625	1	1600	520x520	297	1 core puller
520 C 2000-675	1	2000	520x520	360	1 core puller, several movements possible at the same time, equipped with Geiger discharge handling XYZ
420 C 1000-350/150	1	1000	420x420	153/65	2 components, 1 core puller, rotary table device 2-component synchronous movement
DEMAG ergotech					
500/505-430	1	1000	505x505	205	2 core pullers, 7 integrated hot runner control loops, rotary table with 8 cartoning stations
EXTRA 150-600	1	1500	520x520	290	2 core pullers, 7 integrated hot runner control loops, 1 Wittmann-Handling CNC controlled
250/630-1450	1	2500	630x630	690	2 core pullers, 7 hot runner control loops
350/710-2300	1	3500	710x630	1090	4 core pullers, 7 integr. hot runner control loops, hydr. Holm tensi- oning device, equipped with Geiger-discharge handling XYZ
420/810-3300	1	4200 (4500)	810x710	1600	4 core pullers, 7 integrated hot runner control loops, 1 Wittmann-Handling CNC controlled
IndElect 150/520-410	2	1500	520x520	243	2 core pullers, 16 integrated hot runner control loops